

REDUCED PRESSURE ZONE (RPZ) LAY LENGTH CHART

Manuf.	Model	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	6"	8"	10"
AMES	400B	9 1/2"	12 1/8"	14 1/2"	18 1/8"	18 3/4"	21 1/16"						
	4000B	10"	10 3/4"	16 3/4"	17 3/8"	17 7/8"	21 3/8"						
	4000CIV/5000CIV							41 1/4"	42 1/4"	55 1/8"	65 1/2"	78 1/2"	93 5/8"
	4000RP/5000RPDA									45 1/2"	58 7/8"	68 3/4"	71 3/4"
	4000SS/5000SS		10 3/4"	10 3/4"	10 3/4"	10 3/4"	23 3/4"	37"	38"	40"	48 1/2"	52 1/2"	55 1/2"
	4001/4001SS/ 5001SS	9"	9"	11 1/2"	15 3/8"	15 3/8"			36 1/8"	34 5/8"	43 5/8"		
	C-400/C-500							30 3/4"	31 3/4"	33 3/4"	43 1/2"	49 3/4"	57 3/4"
	M-400/M-500							30 3/4"	31 3/4"	40 1/2"	47 3/4"	54 3/4"	57 3/4"
Buckner	2400		12 1/4"	13 5/8"	17 1/4"	17 1/4"	18 1/2"						
Cla Valve	RP1/RP2		17 1/16"	16 7/8"	21 1/4"	21 11/16"	29 1/4"	42 3/16"	42 3/16"	48 1/4"	61 1/4"	74"	86"
	RP4						33 11/16"	42 3/16"	42 3/16"	48 3/16"	61 3/16"	73 15/16"	85 11/16"
Conbraco	40-200 Series	10 3/4"	13 3/4"	15 3/8"	17 1/2"	19 1/2"	21 1/2"	37 5/16"	38 5/16"	46 3/4"	63 "	75 "	88 3/8"
	4A-200 Series	11 1/8"	12 3/4"	14 5/8"	18 5/8"	18 3/4"	21 1/8"	31"	32 "	38 1/4"	45 7/8"	53 3/8"	62 1/4"
	4D-200 Series							35 1/2"	37 1/2"	39 7/8"	45 5/8"	55"	59"
	4S-200 Series							32 1/4"	33 1/2 "	36 3/4"	42 3/4"	52 3/4"	55 3/4"
Febco	825Y/825YD/825D		12"	12 3/4"	13 5/8"	17"	17 3/4"	37 3/16"	41 11/16"	50 7/16"	59 11/16"	69 3/16"	84 3/16"
	860/866	10"	10 3/4"	12 1/2"	15 7/8"	16 3/8"	17 5/8"	40 3/4"	41 7/8"	46 1/4"	56"	65"	72 5/8"
	867							33 1/4"	34 1/4"				
	880 w/ Flanged Setter							23 1/2"	23 1/2"	27"	32"	36 1/2"	43"
Flomatic	RPZ							31 1/4"	32 1/4"	39"	44 5/8"	52 1/2"	60"
	RPZE		12"	13"	14 3/8"	19"	20"						
	RPZE II	9 1/4"	9 3/4"			17"							

**All dimensions are based on horizontal devices and are approximate inches. **All 1/2" - 2" lengths are Ball Valves. **All 2 1/2" - 10" length are Flanged Gate Valves.

Manuf.	Model	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"	4"	6"	8"	10"
Hersey/ Beeco	FRP II		14 1/4"	15 1/4"	19 3/4"	20 1/4"	23 3/4"						
	6CM (Bronze)							35"	40"	46 1/2"	62"		
	6CM (Cast Iron)							36 1/2"	40"	47 1/2"	62"	75 1/2"	88"
Mueller	H9506		12"	13"		19"	20"	31 1/4"	32 1/4"	39"	46"	52 1/2"	
Rockwell	701						25 1/4"		30 1/4"	35"			
Watts	009	10"	14 3/4"	14 1/2"	21 1/8"	22"	22 3/4"	33 1/4"	34 1/4"				
	009M1				22 1/8"	20 1/4"	21 3/8"						
	009M2		10 3/4"	14 1/2"	17 3/8"	17 7/8"	23 3/8"						
	009M3		10 3/4"										
	900		9"	9"	9 3/16"	14 3/4"	14 3/4"	36 1/2"	37 1/2"	45 11/16"	59 9/16"		
	909/909M1/ 909RPDA		14 3/8"	15 3/8"	18 1/2"	19"	19 1/2"	41 1/4"	42 1/4"	55 1/8"	65 1/2"	78 1/2"	93 5/8"
	919	9 1/2"	12 1/8"	14 1/2"	18 1/8"	18 3/4"	21 1/16"						
	957/957RDPA							30 3/4"	31 3/4"	33 3/4"	43 1/2"	49 3/4"	57 3/4"
	990/990RPDA									46 7/8"	58 3/8"	69 7/8"	
	992/992RDPA									44 7/8"	57 1/4"	59 1/4"	73 1/2"
	994/994RPDA							37"	38"	40"	48 1/2"	52 1/2"	55 1/2"
	995/995RPDA	9"	9"	11 1/2"	15 3/8"	15 3/8"			36 1/8"	34 5/8"	43 5/8"		
Wilkins	DERINGER 40/50							18 7/8"	18 7/8"	18 7/8"		31"	
	375/375ADA	8 7/8"	8 7/8"	11 3/16"	14 7/8"	15 1/4"	16"	31"	32"	37 5/8"	44 3/4"	60 3/4"	63 3/4"
	375A/375ADA							35 1/8"	36 1/8"	38 1/4"	47 1/4"	62"	64 5/8"
	575/575RPDA		13 3/4"	14 3/4"	19 1/4"	19 3/4"	21"	35"	36"	46"	57"		
	975/975XL/975DA	10"	12"	13"	17"	17 3/8"	18 1/2"	37 1/8"	38 1/8"	50 1/4"	62 1/8"	71 1/8"	84 1/8"
	375AST							31 7/8"	32 7/8"	34 7/8"	43 1/2"	52 3/4"	55 3/4"

**All dimensions are based on horizontal devices and are approximate inches. **All 1/2" - 2" lengths are Ball Valves. **All 2 1/2" - 10" length are Flanged Gate Valves.